

RAVENOL Super Turbo 20W-50

SAE: 20W-50

Mineral



1 l

Vendor:
1113126-001



4 l

Vendor:
1113126-004



5 l

Vendor:
1113126-005



10 l

Vendor:
1113126-010



20 l

Vendor:
1113126-020



20 l, ecobox

Vendor:
1113126-B20



60 l

Vendor:
1113126-060



208 l

Vendor:
1113126-208



1 000 l

Vendor:

1113126-700

RAVENOL SUPER TURBO SAE 20W-50 is a universal multigrade engine oil for passenger car gasoline and diesel engines with or without turbocharging. Excellent Features by special solvent refined base oils and special additives. Minimizes friction and wear, good cold start properties. Extended oil change intervals according to manufacturer instructions.

The high additive content of **RAVENOL SUPER TURBO SAE 20W-50** guarantees an excellent effect, especially in regard to the detergent, dispersant and anti-wear properties.

RAVENOL SUPER TURBO SAE 20W-50 is a top product with high safety reserves.

Application Note

RAVENOL SUPER TURBO SAE 20W-50 is used in passenger car gasoline and diesel engines with and without turbocharging, if the SAE 20W-50 is required.

RAVENOL SUPER TURBO SAE 20W-50 is miscible with all HD motor oils based on mineral oil.

Characteristics

- Excellent detergent and dispersant
- A good cold start performance
- High oxidation stability
- An excellent viscosity-temperature behaviour
- Best wear protection
- High safety reserves
- Reduction of emissions
- Catalyst suitability

Characteristics

<i>Title</i>	<i>Value</i>	<i>Audit</i>
API	CF, CH-4, SL	
ACEA	A3, B4, E2	
Complies with manufacturer's requirements	Cummins CES 20071, Deutz DQC II-10, MAN 271, MB 228.1, MB 229.1, MTU Type 1, Mack EO-M, VW 501.01, VW 505.00, Volvo VDS	
Density at 20 °C	876,0	EN ISO 12185
Color	Brown	visual
Viscosity at 100 °C	18.9 mm ² /s	DIN 51562-1
Viscosity at 40 °C	161.2 mm ² /s	DIN 51562-1
Viscosity Index VI	133	DIN ISO 2909
CCS Viscosity at -15 °C	6500 mPa*s	ASTM D5293
Pourpoint	-30 °C	DIN ISO 3016
Flashpoint	241 °C	DIN EN ISO 2592
TBN	11.3 mgKOH/g	ASTM D2896