

RAVENOL Sperrdiff. Hyp. Getr.öl LS 80W-90 GL-5

SAE: 80W-90**Mineral****1 l**Vendor:
1223303-001**4 l**Vendor:
1223303-004**10 l**Vendor:
1223303-010**20 l**Vendor:
1223303-020**20 l, ecobox**Vendor:
1223303-B20**60 l**Vendor:
1223303-060**208 l**Vendor:
1223303-208**1 000 l**Vendor:
1223303-700

Characteristics

<i>Title</i>	<i>Value</i>	<i>Audit</i>
API	GL-5	
Complies with manufacturer's requirements	ZF TE-ML 05C, ZF TE-ML 12C, ZF TE-ML 16E	
Conforms to manufacturer's specifications	MIL-L-2105 D	
Density at 20 °C	889 kg/m ³	EN ISO 12185
Color	tan	visual
Viscosity at 100 °C	17.6 mm ² /s	DIN 51562-1
Viscosity at 40 °C	177.3 mm ² /s	DIN 51562-1
Viscosity Index VI	108	DIN ISO 2909
Brookfield Viscosity at -26 °C	114.400 mPa*s	ASTM D2983
Pourpoint	-33 °C	DIN ISO 3016
Flashpoint	214 °C	DIN EN ISO 2592
Copper Strip Test at 121 °C	1b	ASTM D130