

RAVENOL ODL 68 Druckluftoel

SAE: 68

**208 l**

Vendor:

1323406-208

RAVENOL ODL 68 Druckluftoel is a special-compressed-air-oil for pneumatic tools of all systems.

RAVENOL ODL 68 Druckluftoel bonds condensed water, has an excellent corrosion protection, wear protection and an extraordinary pressure absorption capacity, a good adhesive power and high aging resistance. Easily conveying- and spray ability, economy consumption. No deposits caused by cleaning effects. Full power of impact.

Application Note

RAVENOL ODL 68 Druckluftoel is specially suitable for pneumatic tools with sound-absorbing-case, for lubrication of rock drills, road breaker, chipping hammer and spade hammer, ram machines and other pneumatic aggregates. Application by pre-switch-lubricator according to working instructions or usable directly in the air pipe. Please follow the manufacturer's instructions.

Characteristics

- a high performance level
- a very good viscosity temperature behaviour
- a high aging resistant
- an excellent corrosion protection
- a solid corrosion protection
- neutrality of sealing materials

Characteristics

<i>Title</i>	<i>Value</i>	<i>Audit</i>
Complies with manufacturer's requirements	Black & Decker	
Suitable for	Atlas Copco Kompressor, Bosch, Cress, DeWalt, Festo, Hilti, Hitachi, Makita, Ryobi, Seno, Sumake	
Density at 20 °C	866 kg/m ³	EN ISO 12185
Color	light yellow	visual
Viscosity at 100 °C	9 mm ² /s	DIN 51562-1
Viscosity at 40 °C	68 mm ² /s	DIN 51562-1
Viscosity Index VI	106	DIN ISO 2909
Pourpoint	-27 °C	DIN ISO 3016
Flashpoint	256 °C	DIN EN ISO 2592

Out of production

<i>Product</i>	<i>Vendor</i>	<i>Barcode</i>
208 l	1323406-208-01-999	