

RAVENOL SCR 68 Screw Kompressorenöl

SAE: 68

Mineral



5 l

Vendor:
1330306-005



20 l

Vendor:
1330306-020



60 l

Vendor:
1330306-060



208 l

Vendor:
1330306-208

RAVENOL Screw Kompressorenöl SCR 68 is optimal alloyed, has a high performance level and a wide application area of the whole industry. It is characterised by a good viscosity temperature behaviour, a high aging resistant and a solid corrosion protection. Efficient additives offer an excellent corrosion protection even under extreme loads. The behaviour of sealing materials is neutral.

Application Note

RAVENOL Screw Kompressorenöl SCR 68 is used in compressors.

Characteristics

- a high performance level
- a very good viscosity temperature behaviour
- a high aging resistant
- an excellent corrosion protection
- a solid corrosion protection

- neutrality of sealing materials

Characteristics

<i>Title</i>	<i>Value</i>	<i>Audit</i>
Complies with manufacturer's requirements	FZG Test A 8,3/90, Sperry Vickers I-286-S, Sperry Vickers M-2950-S, Vickers Pumpentest	
Conforms to manufacturer's specifications	DIN 51524-2	
Density at 20 °C	866 kg/m ³	EN ISO 12185
Color	light yellow	visual
Viscosity at 100 °C	9 mm ² /s	DIN 51562-1
Viscosity at 40 °C	68 mm ² /s	DIN 51562-1
Viscosity Index VI	106	DIN ISO 2909
Pourpoint	-27 °C	DIN ISO 3016
Flashpoint	256 °C	DIN EN ISO 2592
Damage loading step	12	DIN 51354/2
Aging stability, TOST	2000 st	DIN 51587

Out of production

<i>Product</i>	<i>Vendor</i>	<i>Barcode</i>
5 l	1330306-005-01-999	
20 l	1330306-020-01-999	
60 l	1330306-060-01-999	
208 l	1330306-208-01-999	