

# RAVENOL Getriebeoel CLP 32

**SAE: 32W****Mineral****20 l**

Vendor:

**1332104-020**

RAVENOL Getriebeoel CLP 32

is a high quality, mineral-based gear oil formulated with selected high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity.

RAVENOL Getriebeoel CLP 32

has a low pour point and therefore a very good cold behaviour.

## Application Note

### RAVENOL Getriebeoel CLP 3

can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

## Characteristics

<i>Title</i>	<i>Value</i>	<i>Audit</i>
Complies with manufacturer's requirements	AGMA 9005-D94, Clean Panel Coker, S-200 Oxidation Tubes, U.S. Steel 224	
Conforms to manufacturer's specifications	DIN 51517-3	
Suitable for	Cincinnati Milacron	
Density at 20 °C	854 kg/m <sup>3</sup>	EN ISO 12185
Color	Yellow	visual
Viscosity at 100 °C	6 mm <sup>2</sup> /s	DIN 51562-1
Viscosity at 40 °C	34.6 mm <sup>2</sup> /s	DIN 51562-1
Viscosity Index VI	119	DIN ISO 2909
Pourpoint	-30 °C	DIN ISO 3016
Flashpoint	205 °C	DIN EN ISO 2592

## Out of production

<i>Product</i>	<i>Vendor</i>	<i>Barcode</i>
20 l	1332104-020-01-999	