

RAVENOL Super HD 50

Вискозност: 50W

Минерално уље



1 л

Чланак:
1113305-001
Чланак:
1113305-001-01-999



4 л

Чланак:
1113305-004
Чланак:
1113305-004-01-999



5 л

Чланак:
1113305-005
Чланак:
1113305-005-01-999



10 л

Чланак:
1113305-010



20 л

Чланак:
1113305-020
Чланак:
1113305-020-01-999



20 л, есобох

Чланак:
1113305-B20



60 л

Чланак:
1113305-060
Чланак:
1113305-060-01-999



60 л, штампано буре

Чланак:
1113305-D60



208 л

Чланак:

1113305-208

Чланак:

1113305-208-01-999



1 000 л

Чланак:

1113305-700

Extended oil drain capability where recommended by the vehicle manufacturer.

Application Note

RAVENOL Super HD 50 is suitable for both gasoline and diesel engines in cars, van and commercial vehicles with and without turbocharging under light loads which require this SAE 50 grade of oil.

Characteristics

- Good shear stability
- High oxidation stability
- Excellent viscosity-temperature behavior
- Enhanced levels of detergent and dispersant for cleaner engines
- Very good cold starting properties
- Prevents formation of deposits and black sludge
- High safety reserves even under boundary lubrication conditions
- Catalyst suitability

Карактеристике

Име	Значење	Ревизија
API	CD, SF	
Испуњава захтеве	CCMC D1, CCMC G2, Ford ESE-M2C 153-C, Ford SMM-2C 9011A, GM 6085M, MIL-L-46152 B, MIL-L-46152 C	
Густина на 20°C	889 г/цм³	EN ISO 12185
Боја	Жуто-браон	visual
Вискозност на 100°C	18.4 мм²/с	DIN 51562-1
Вискозност на 40°C	200.1 мм²/с	DIN 51562-1
Индекс вискозности VI	102	DIN ISO 2909
Тачка стињавања	-21 °Ц	DIN ISO 3016
Температура паљења	278 °Ц	DIN EN ISO 2592
Основни број	7.4 мгКОХ/г	ASTM D2896

Укинуто паковање

Паковање	Чланак	Баркод
1 л	1113305-001-06-999	
10 л	1113305-010-01-999	