

# RAVENOL Super Truck 40

Вискозност: 40W

Минерално уље



**1 л**

Чланак:  
**1123725-001**



**5 л**

Чланак:  
**1123725-005**



**10 л**

Чланак:  
**1123725-010**



**20 л**

Чланак:  
**1123725-020**



**20 л, есобоx**

Чланак:  
**1123725-B20**



**60 л**

Чланак:  
**1123725-060**



**208 л**

Чланак:  
**1123725-208**



**1 000 л**

Чланак:  
**1123725-700**

**RAVENOL Super Truck SAE 40** is a top-quality product with high safety reserves.

## **Application Note**

**RAVENOL Super Truck SAE 40** is mono grade motor oil for use in truck diesel engines with or without turbo charger.

Please follow engine manufacturer's recommendations.

## **Characteristics**

- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- Good cold start characteristics
- Best corrosion protection
- High safety reserves even with boundary lubrication conditions
- Suitable for catalysts

## Карактеристике

Име	Значење	Ревизија
API	CF-4, SG	
ACEA	B4, E2	
Испуњава захтеве	Allison C-4, Caterpillar TO-2, Deutz DQC I-02, MAN 270, MB 228.0, MB 235.12, MIL-L-2104 D, MTU Type 1, ZF TE-ML 02H, ZF TE-ML 04A, ZF TE-ML 04B	
Густина на 20°C	883 г/цм <sup>3</sup>	EN ISO 12185
Боја	Бровн	visual
Вискозност на 100°C	14.3 мм <sup>2</sup> /с	DIN 51562-1
Вискозност на 40°C	131.5 мм <sup>2</sup> /с	DIN 51562-1
Индекс вискозности VI	108	DIN ISO 2909
Тачка стињавања	-21 °Ц	DIN ISO 3016
Температура паљења	246 °Ц	DIN EN ISO 2592

## Укинуто паковање

Паковање	Чланак	Баркод
1 л	1123725-001-06-999	
5 л	1123725-005-01-400 1123725-005-01-999	
10 л	1123725-010-01-999	
20 л	1123725-020-01-400 1123725-020-01-999	
208 л	1123725-208-01-999	