

RAVENOL Gas Engine Oil LFG 40

ВИСКОЗНОСТ: 40W

Минерално



20 l

артикал:
1133106-020



20 l, ecobox

артикал:
1133106-B20



60 l

артикал:
1133106-060



208 l

артикал:
1133106-208



1 000 l

артикал:
1133106-700

Карактеристике

Име	Значење	Ревизија
Одобрен произвођач	MAN M 3271-4 (special gas), MAN M 3271-5	
Испуњава захтеве	General Electric Jenbacher General Electric Jenbacher Type 2 (A & B) - Gas B & C, General Electric Jenbacher Type 3 (A & B) - Gas B & C, General Electric Jenbacher Type 4 (A & B) - Gas B & C, General Electric Jenbacher Type 6 (C & E) - Gas B & C	
Погодан за	Caterpillar CG gas engines, MWM TCC gas engines	
Густина на 20°C	879 g/cm ³	EN ISO 12185
Боја	Браон	визуелни
Вискозност на 100°C	13.5 mm ² /s	DIN 51659-2
Вискозност на 40°C	129.1 mm ² /s	DIN 51659-2
Индекс вискозности VI	100	DIN ISO 2909
Тачка стињавања	-21 °C	DIN ISO 3016
Температура паљења	276 °C	DIN EN ISO 2592
Волатилност NOACK	3 %	ASTM D5800
Препоруке	General Electric Jenbacher Typ 2 (A & B) - Gas B & C, General Electric Jenbacher Typ 3 (A & B) - Gas B & C, General Electric Jenbacher Typ 4 (A & B) - Gas B & C, General Electric Jenbacher Typ 6 (C & E) - Gas B & C	
Тест бакарне траке на 150°C	1b	ASTM D130
Високотемпературни вискозитет (HTHS) на 150°C	3.91 mPa*s	ASTM D5481
Основни број	4.4 mgKOH/g	ASTM D2896