

RAVENOL MARINEOIL DIESEL SHPD 10W-40

Вискозност: 10W-40

Полусинтетичко уље



1 л

Чланак:
1162100-001



4 л

Чланак:
1162100-004



10 л

Чланак:
1162100-010



20 л

Чланак:
1162100-020



20 л, esobox

Чланак:
1162100-B20



60 л

Чланак:
1162100-060



208 л

Чланак:
1162100-208



1 000 л

Чланак:
1162100-700

RAVENOL MARINEOIL DIESEL SHPD 10W-40 is produced with unconventional and HC basic oils, synthetic components and modern additives.

RAVENOL MARINEOIL DIESEL SHPD 10W-40 guarantees longest oil change intervals and a high corrosion protection with a low oil and fuel consumption.

Application Note

RAVENOL MARINEOIL DIESEL SHPD 10W-40 is tried and tested for aggregates specifying:

Specifications: API CI-4/CF, ACEA E7, B4

Recommendations: Caterpillar, Detroit Diesel, IVECO, MAN, Mercruiser, MTU, NANNI Diesel, PERKINS, SKL, Steyr, SULZER, VETUS DEUTZ, VOLVO PENTA, Yanmar

Characteristics

- Excellent detergent and dispersant characteristics
- Low evaporation
- High aging stability
- Protection of reflecting surface formation
- Very good cold start characteristics
- Reduces oil and fuel consumption

Карактеристике

Име	Значење	Ревизија
API	CF, CI-4, SL	
ACEA	A3, B4, E7	
Испуњава захтеве	DDC Detroit Diesel, Scania LDF-2, VETUS DEUTZ, Volvo PENTA	
Погодан за	Caterpillar, IVECO, MAN, MTU, Mercruiser, NANNI Diesel, PERKINS, SKL, STEYR, SULZER, Yanmar	
Густина на 20°C	866 г/цм ³	EN ISO 12185
Боја	Плави	visual
Вискозност на 100°C	13.7 мм ² /с	DIN 51562-1
Вискозност на 40°C	92 мм ² /с	DIN 51562-1
Индекс вискозности VI	151	DIN ISO 2909
Ниска температура вискозитета (CCS) на -25°C	6470 мПа*с	ASTM D5293
Тачка стињавања	-36 °Ц	DIN ISO 3016
Температура паљења	214 °Ц	DIN EN ISO 2592
Основни број	11 мгКОХ/г	ASTM D2896
Садржај сулфатног пепела	1.3 %wt.	DIN 51575

Укинуто паковање

Паковање	Чланак	Баркод
1 л	1162100-001-01-999 1162100-001-06-999	
4 л	1162100-004-01-999	
10 л	1162100-010-01-999	
20 л	1162100-020-01-999	
60 л	1162100-060-01-999	
208 л	1162100-208-01-999	