

# RAVENOL MARINE 1630 30 TBN16

Вискозност: 30W

Минерално уље



**1 л**

Чланак:  
**1163020-001**  
Чланак:  
1163020-001-01-999



**4 л**

Чланак:  
**1163020-004**  
Чланак:  
1163020-004-01-999



**10 л**

Чланак:  
**1163020-010**



**20 л**

Чланак:  
**1163020-020**  
Чланак:  
1163020-020-01-999



**20 л, esobox**

Чланак:  
**1163020-B20**



**60 л**

Чланак:  
**1163020-060**  
Чланак:  
1163020-060-01-999



**208 л**

Чланак:  
**1163020-208**  
Чланак:  
1163020-208-01-999



**1 000 л**

Чланак:  
**1163020-700**

**RAVENOL MARINE 1630 SAE 30 TBN16** is made from high quality solvent refined basic oils with a special multi functional additivation for the demands of a navy oil for the use of navy diesel engines and for the lubrication of gear transfers in aggregates used on boats.

## Application Note

**RAVENOL MARINE 1630 SAE 30 TBN16** is used as a lubrication oil in quickly running and so-called « medium speed » navy diesel engines, perhaps with turbo charging and when using distilled fuels with asulfur content up to 1,8 %.

**RAVENOL MARINE 1630 SAE 30 TBN16** can also be used for the lubrication of gear transfers in aggregates used on boats.

## Characteristics

- a very good oxidation resistance
- a stable viscosity index
- excellent dispersant and detergent characteristics
- a good neutralizing power to neutralize acid connections which occur when burning diesel fuels
- a good cleaning power
- a good corrosion protection
- a good foam prevention
- a low pourpoint
- a good water separation behaviour

## Карактеристике

Име	Значење	Ревизија
API	CF	
Испуњава захтеве	DEF 91-22/2, MIL-L-2104 C	
Испуњава спецификације	SAE 30	
Густина на 20°C	890 г/цм <sup>3</sup>	EN ISO 12185
Боја	Бровн	visual
Вискозност на 100°C	11.5 мм <sup>2</sup> /с	DIN 51562-1
Вискозност на 40°C	101.5 мм <sup>2</sup> /с	DIN 51562-1
Индекс вискозности VI	100	DIN ISO 2909
Тачка стињавања	-21 °Ц	DIN ISO 3016
Температура паљења	245 °Ц	DIN EN ISO 2592
Основни број	16 мгКОХ/г	ASTM D2896
Садржај сулфатног пепела	2.21 %wt.	DIN 51575
Ход мотора	4Т	

## Укинуто паковање

Паковање	Чланак	Баркод
1 л	1163020-001-06-999	
10 л	1163020-010-01-999	