

RAVENOL MARINE 1640 40 TBN16

Вискозност: 40W**Минерално уље****1 л**

Чланак:
1163021-001
Чланак:
1163021-001-01-999

**4 л**

Чланак:
1163021-004
Чланак:
1163021-004-01-999

**10 л**

Чланак:
1163021-010

**20 л**

Чланак:
1163021-020
Чланак:
1163021-020-01-999

**20 л, esobox**

Чланак:
1163021-B20

**60 л**

Чланак:
1163021-060
Чланак:
1163021-060-01-999

**208 л**

Чланак:
1163021-208
Чланак:
1163021-208-01-999

**1 000 л**

Чланак:
1163021-700

RAVENOL MARINE 1640 SAE 40 TBN16 is made from high quality solvent refined basic oils with a special multi functional additivation for the demands of a navy oil for the use of navy diesel engines and for the lubrication of gear transfers in aggregates used on boats.

Application Note

RAVENOL MARINE 1640 SAE 40 TBN16 is used as a lubrication oil in quickly running and so-called « mediumspeed » navy diesel engines, perhaps with turbo charging and when using distilled fuels with a sulfur content upto 1,8 %.

RAVENOL MARINE 1640 SAE 40 TBN16 can also be used for the lubrication of gear transfers in aggregates used on boats.

Characteristics

- a very good oxidation resistance
- a stable viscosity index
- excellent dispersant and detergent characteristics
- a good neutralizing power to neutralize acid connections which occur when burning diesel fuels
- a good cleaning power
- a good corrosion protection
- a good foam prevention
- a low pourpoint
- a good water separation behaviour

Карактеристике

Име	Значење	Ревизија
API	CF	
Испуњава захтеве	DEF 91-22/2, MIL-L-2104 C	
Испуњава спецификације	SAE 40	
Густина на 20°C	893 г/цм ³	EN ISO 12185
Боја	Бровн	visual
Вискозност на 100°C	14.5 мм ² /с	DIN 51562-1
Вискозност на 40°C	146 мм ² /с	DIN 51562-1
Индекс вискозности VI	97	DIN ISO 2909
Тачка стињавања	-18 °Ц	DIN ISO 3016
Температура паљења	268 °Ц	DIN EN ISO 2592
Основни број	17.4 мгКОХ/г	ASTM D2896
Садржај сулфатног пепела	2.21 %wt.	DIN 51575
Ход мотора	4Т	

Укинуто паковање

Паковање	Чланак	Баркод
1 л	1163021-001-06-999	
10 л	1163021-010-01-999	