

RAVENOL MARINEOIL PETROL 20W-50

Вискозност: 20W-50**Минерално уље****1 л**Чланак:
1163210-001**4 л**Чланак:
1163210-004
Чланак:
1163210-004-01-999
Баркод:
4014835730397**10 л**Чланак:
1163210-010**20 л**Чланак:
1163210-020**20 л, esobox**Чланак:
1163210-B20**60 л**Чланак:
1163210-060**208 л**Чланак:
1163210-208**1 000 л**Чланак:
1163210-700

RAVENOL MARINEOIL PETROL 20W-50 corresponds to the demands of the SAE class 20W-50. This viscosity classification guarantees a good lubricating film also under complicate operating conditions.

Characteristics

- an extreme high pressure absorption capacity
- a very high oxidation stability
- an excellent aging resistance
- an excellent viscosity temperature behaviour
- high safety reserves also under boundary lubrication conditions
- suitability for extended oil change intervals
- suitability for complicate operating conditions
- a good water separation behaviour

Карактеристике

Име	Значење	Ревизија
API	SL	
Испуњава захтеве	Volvo Penta AB	
Погодан за	Kohler, Mercruiser, Yanmar	
Густина на 20°C	878.2 г/цм ³	EN ISO 12185
Боја	Плави	visual
Вискозност на 100°C	18.5 мм ² /с	DIN 51562-1
Вискозност на 40°C	161 мм ² /с	DIN 51562-1
Индекс вискозности VI	129	DIN ISO 2909
Тачка стињавања	-36 °Ц	DIN ISO 3016
Температура паљења	247 °Ц	DIN EN ISO 2592
Основни број	10.7 мгКОХ/г	ASTM D2896
Садржај сулфатног пепела	1.42 %wt.	DIN 51575
Ход мотора	4Т	

Укинуто паковање

Паковање	Чланак	Баркод
1 л	1163210-001-01-999 1163210-001-06-999	
10 л	1163210-010-01-999	
20 л	1163210-020-01-999	
60 л	1163210-060-01-999	
208 л	1163210-208-01-999	