

RAVENOL Truck MTF-50

Потпуно синтетички



1 л

Чланак:
1221106-001
Чланак:
1221106-001-01-999



4 л

Чланак:
1221106-004
Чланак:
1221106-004-01-999



10 л

Чланак:
1221106-010



20 л

Чланак:
1221106-020
Чланак:
1221106-020-01-999



60 л

Чланак:
1221106-060
Чланак:
1221106-060-01-999



208 л

Чланак:
1221106-208
Чланак:
1221106-208-01-999

RAVENOL Truck MTF-50 is based on synthetic base oils and special additives matched to them. Thus, the extended requirements of Eaton axle and transmission divisions are fulfilled.

RAVENOL Truck MTF-50 is ideally suited for severe operating conditions and extended oil change intervals.

Application Note

RAVENOL Truck MTF-50 is recommended for extended drain and severe service in heavy duty (class 6, 7, and 8) manual transmissions requiring a non-EP lubricant.

Characteristics

- Excellent thermal stability.
- Strong protection against rust, corrosion and foaming.
- A very low pour point.
- Excellent EP properties.
- A good switching behavior at low temperatures.
- An extended service life.
- Fuel savings.

Карактеристике

Име	Значење	Ревизија
API	MT-1	
Испуњава захтеве	Arvin Meritor 0-81, Eaton PS-164 Rev. 7, International Harvester TMS-6816, Mack TO-A Plus, ZF FreedomLine, ZF TE-ML 02L	
Густина на 20°C	857 г/цм ³	EN ISO 12185
Боја	Бровн	visual
Вискозност на 100°C	17.5 мм ² /с	DIN 51562-1
Вискозност на 40°C	132 мм ² /с	DIN 51562-1
Индекс вискозности VI	146	DIN ISO 2909
Вискозност, Брукфилд на -26°C	16.900 мПа*с	ASTM D2983
Тачка стињавања	-45 °Ц	DIN ISO 3016
Температура паљења	221 °Ц	DIN EN ISO 2592
Испитивање корозије бакра, на 121°C / 3х	1а	ASTM D130

Укинуто паковање

Паковање	Чланак	Баркод
10 л	1221106-010-01-999	