

RAVENOL Hydraulikoel TS AF 22

Вискозност: 22**Минерално уље****20 л**

Чланак:
1323123-020
Чланак:
1323123-020-01-999

**208 л**

Чланак:
1323123-208
Чланак:
1323123-208-01-999

**1 000 л**

Чланак:
1323123-700

is a zinc and ash-free compounded oil based phosphorous and sulfur intended especially for use in the metal industry. Excellent results were achieved in the Timken test. Through the addition of selected ingredients,

RAVENOL Hydraulikoel TS AF 22

has excellent wear protection, good oxidation stability and has a long service life even under extreme conditions. Compatibility with sealants is neutral. Furthermore, the additives provide corrosion protection and prevent foaming.

RAVENOL Hydraulikoel TS AF 22

exceeds the requirements of DIN 51 524 part 2 for HLP hydraulic oils.

Application Note

RAVENOL Hydraulikoel TS AF 2

is for use as a hydraulic fluid in the metal industry, if zinc and ash-free hydraulic oil and the specification DIN 51 524, Part 2 is required.

Карактеристике

Име	Значење	Ревизија
Испуњава захтеве	MAN N 698, SEB 181.222, SEB 181.226, Timken-Test DIN E 51434	
Испуњава спецификације	DIN 51524-2	
Густина на 20°C	857 g/cm ³	EN ISO 12185
Боја	Жута	visual
Вискозност на 100°C	4.3 mm ² /s	DIN 51562-1
Вискозност на 40°C	22 mm ² /s	DIN 51562-1
Индекс вискозности VI	103	DIN ISO 2909
Тачка стињавања	-39 °C	DIN ISO 3016
Температура паљења	206 °C	DIN EN ISO 2592