

RAVENOL Hydraulikoel HLP-D 68

Вискозност: 68**Минерално уље****60 л**

Чланак:

1323306-060

Чланак:

1323306-060-01-999

RAVENOL Hydraulikoel HLP-D 68 is designed with selected base oils with additives to prevent corrosion, wear and friction.

RAVENOL Hydraulikoel HLP-D 68 also contains detergent and dispersing agents, which always provide for a clean hydraulic system. These additives dissolve contaminants, hold them in suspension and enabling the cleaning of contaminated hydraulic systems. The functional elements of a hydraulic system thereby remain free of deposits and bonds. This will emulsified penetrating water and ensure trouble-free operation of the hydraulic system.

Application Note

RAVENOL Hydraulikoel HLP-D 68 is for use in agriculture hydraulic systems, construction machinery, cement factories, foundries, and electro-plate clutches. It can also be used as functional test oil, inlet oil for aggregates and machinery, textile machinery and machine tools.

Characteristics

- High aging resistance and high corrosion protection
- Good air release
- Excellent wear protection and proper conduct foam
- Very good viscosity-temperature behaviour
- neutral behaviour towards sealing materials
- Extremely good detergent and dispersant characteristics
- Excellent corrosion protection even at the ingress of wetness

Карактеристике

Име	Значење	Ревизија
Испуњава захтеве	Daimler DBL 6721, MAN N 698, Parker Denison HF-0	
Испуњава спецификације	DIN 51524-2	
Густина на 20°C	869 g/cm ³	EN ISO 12185
Боја	Жуто-браон	visual
Вискозност на 100°C	9.4 mm ² /s	DIN 51562-1
Вискозност на 40°C	69.2 mm ² /s	DIN 51562-1
Индекс вискозности VI	113	DIN ISO 2909
Тачка стињавања	-36 °C	DIN ISO 3016
Температура паљења	234 °C	DIN EN ISO 2592